

3.6W COB INDOOR LED TAPE LIGHT (2700K)

DOT LESS

1936-24V-27K



PROJECT

DESCRIPTION


This high-output LED spotless tape light delivers smooth, continuous illumination with no visible LED hot spots. Consuming only 3.6 watts per foot, it provides excellent brightness while maintaining high energy efficiency. With 90+ CRI for accurate color rendering, UL Listed construction, and dimmable performance, it is an ideal choice for cove lighting, under-cabinet applications, architectural details, and other residential or commercial installations.

SPECIFICATION DETAILS

Dimensions	L 16.4" per Role
Light Source	DC LED Module
Power	3.6W / FT
Total Lumen	348 lm / FT
Delivered Lumen	348 lm
Input Voltage	24V DC
Color Temperature	2700K
CRI (Ra)	90 + CRI
LED Rated Life	60,000 hours
Dimmable	Yes
Diffuser Details	180° Beam Angle
Environment	Dry / Damp indoor IP20
Mounting	Ceiling / Wall / Channels
Working Temp	-4~104
Cut Points	1.5"
Lead wire	6"
Driver	Requires 24V DC LED Driver
Standards	UL listed JA8 Title24



Color Vector Graphic LED Tape Light




Red Test Blue Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%

2700K Color Temperature 3.6 W/ft Power Consumption 150° Beam Angle CRI 90 Color Rendering Index 360 lm/ft Luminous Flux


ACCESSORIES



L connector



Tape-to-Tape



Live End

COMMENT

