RAYCOS LIGHTING

PROJECT NAME _____ DATE _____

NOTE _____

BEAM HIGH BAY SERIES

BEAM 4 FT LED HIGH BAY

SELECTABLE POWER + COLOR



LENGTH
4 FT

POWER
220 / 190 / 160 W

OUTPUT
30,800 LM @ 220 W

COLOR
3500 / 4000 / 5000 K

APPLICATION

WAREHOUSE + INDUSTRIAL



PRODUCT FEATURES

COMMERCIAL-GRADE

- Replaces fluorescent and metal-halide high bays
- Operating range: -40 F to 122 F (-40 C to 50 C)
- IP20 rated and suitable for damp locations
- Lumen maintenance over 70% at 50,000+ hours
- 110-degree beam for broad, even distribution
- White finish with aluminum heatsink
- Frosted or prismatic PMMA lens, depending on model

ORDERING GUIDE

BEAM 4 FT CONFIGURATION

Model	Selectable Power	Selectable CCT	Max Output	CRI / PF	Input	Dimming
RY-LHB-220W4FT-H-3W3CCT	220 / 190 / 160 W	3500 / 4000 / 5000 K	30,800 lm @ 220 W	>80 / >=0.9	120-277 VAC	0-10 V

MOUNTING HEIGHT
16-26 FT

BEAM
110 DEG

RATING
IP20 / DAMP

RATED LIFE
50,000+ HRS

DLC
S-FESPTK

INCLUDED ACCESSORIES

HOOK + CHAIN



HOOKS

Included suspension hardware



CHAINS

Included suspension hardware

OPTIONS ORDERING GUIDE

SENSOR + EMERGENCY

Type	Option Model	Function
Motion Sensor	**ANT-5-4T**	Microwave motion sensor
Motion Sensor (Max. 40 ft)	**ANT-6-4T**	PIR motion sensor with bi-level control
Motion Sensor (Max. 50 ft)	**HD09VR-MH-1**	Microwave on/off or bi-level control with daylight harvesting
Emergency Driver	**BLD-HM25D-480800**	Emergency backup driver