

SPECIFICATIONS

FEATURE

- Featuring tunable White Color Temperature: 3000K, 4000K and 5000K
- Adjustable Wattage to meet different customer demand
- 0-10V Dimmable
- Body: Aluminum Heatsink for Efficient Heat Dissipation
- Diffusers are extruded from impact modified acrylic for increased durability
- Multiple type combination connection
- High efficiency: 130lm/w, DLC premium listed
- WARRANTY--5-year limited warranty



APPLICATION

- Office; hotel; conference room; display room; school/installation; retails...

SPECIFICATIONS

Model No.		HY -4FT-LUD-50W-30K/40K/50K				
Power:	25W	50W	100W	12W	12W	15W
Size:		4ft		L Shape	T Shape	CROSS Shape
Input Voltage:	120-277 VAC					
Dimming	0-10V Dimmable					
Lumens	3250 LM	6500 LM	13000 LM	1560 LM	1560 LM	1950 LM
Protection Rating	IP20 (For Indoor Use Only)					
Power Factor:	>0.9					
Beam Angle	100°					
CCT:	3000K/4000K/5000K					
CRI:	>80					
Working Life:	Lumen Maintenance over 70% @ 50,000+ Hours					
Oper. Temperature	-13°F ~+113°F / -25°C ~+45°C					
Certification	DLC Premium / ETL					