

Slim Flood Light

5CCT & PHOTOCELL

```
Catalog Number:
```

Project Name :

Note:

Date:

DESCRIPTION

The Slim Flood Light is a versatile and energy-efficient outdoor lighting solution, designed for maximum flexibility and durability. Featuring 5CCT selectable technology (2700K, 3000K, 3500K, 4000K, and 5000K), it allows users to customize the color temperature to suit different environments. Equipped with a built-in photocell and an on/off switch, it offers automated dusk-to-dawn operation for convenience and energy savings. This fixture is UL Listed for wet locations, ensuring reliable performance in harsh weather conditions.




BASED ON SAMPLE SETTING.ACTUAL LUMENS MAY VARY

MODEL#	WATTAGE	5CCT	LUMENS
		2700K	1510L
		3000K	1545L
FLE-15-120-8SC53-K-BR-P 15W		3500K	1580L
		4000K	1600L
		5000K	1630L
MODEL#	WATTAGE	5CCT	LUMENS
		2700K	16540L
		3000K	16610L
FLE-50-120-8SC53-K-BR-	-P 50W	3500K	16850L
		4000K	16720L
		5000K	16900L

TECHNICAL SPECIFICATION		
VOLTAGE	120V	
POWER FREQUENCY	60Hz	
POWER FACTOR	>0.9	
5CCT	2700K 3000K 3500K 4000K 5000K	
CRI	80	
BEAM ANGLE	110°	
MATERIAL	AL+PC	
LIFESPAN	≥50,000hours	
OPERATING TEMP	(-4°F~ 113°F) -20~45°C	
DIMMABLE	Non Dimming	
RATING	Wet Locations	

WARRANTY

3 year limited



FEATURES

- Slim and Compact profile
- Biult in Photocell with ON/OFF switch
- 90+ CRI, superior color rendering performance
- Architectural Bronze Finish

DIMMING

Not Dimmable

ENERGY SAVINGS

80% more energy savings than halogen lamps.

INSTALLATION

1/2" Outdoor electrical box

LIFESPAN

This luminaire is built with the highest quality 120V drivers, ensuring energy efficiency. With a lifespan of 50,000 hours, it can last decades under normal operation!

