

RY-3R-SMOOTH-5CCT

DESCRIPTION

This 3 inch LED retrofit trim delivers efficient, high quality illumination with a 5CCT switch that allows you to select from multiple color temperatures to suit any space. Using just 9 watts while producing approximately 650 lumen, it provides bright, energy-saving performance ideal for residential or light commercial applications. The fixture is UL listed for safety and tested reliability, and its JA8 / California Title 24 compliance makes it an excellent choice for meeting current California energy code requirements in new construction or retrofit projects.



BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
RY-3R-SMOOTH-5CCT	3inch	9W	2700K	611lm
			3000K	618lm
			3500K	625lm
			4000K	635lm
			5000K	650lm

TECHNICAL SPECIFICATION

WATTAGE	9W
VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	90
BEAM ANGLE	120°
MATERIAL	Meta + Composite
LIFESPAN	≥50,000hours
DIMMABLE	Triac Dimmable
Lumens per Watt	72.2 lm / w
BASE	E26 Conversion included
EMERGENCY TIME	NA
INITIAL CHARGE TIME	NA
BATTERY TYPE	NA
LED INDICATOR	NA
OPERATING TEMP.	-20/45°C
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

DESCRIPTION

- 3 inch Smooth Retrofit Down light 5CCT 9W 650LM

INSTALLATION

Compatible with 3 Inch Housing

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-5% dimming to choose the desired brightness. Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

UL Listed. Energy Star. Title24.



H3-ICAT-R



H3-ICAT-NC