

Catalog Number:

Project Name:

Note:

Date:

Type:

RY-3R-SLIM-5CCT

DESCRIPTION

The 3-inch slim recessed LED light delivers a low-profile, modern lighting solution ideal for applications with limited plenum space. Featuring 5CCT selectable color temperatures, it provides flexible lighting options to suit a variety of environments. This fixture is UL listed for safety and reliability and includes an external LED driver that is fully compatible with the mounting plate for easy and secure installation. Designed for both residential and light commercial use, it offers efficient performance, clean aesthetics, and dependable operation.


BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
			2700K	311lm
			3000K	318lm
RY-3R-SLIM-5CCT	3inch 5W		3500K	325lm
			4000K	335lm
			5000K	350lm

TECHNICAL SPECIFICATION

WATTAGE	5W
VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	90
BEAM ANGLE	120°
MATERIAL	Meta + Composite
LIFESPAN	≥50,000hours
DIMMABLE	Triac Dimmable
Lumens per Watt	70 lm / w
BASE	E26 Conversion included
EMERGENCY TIME	NA
INITIAL CHARGE TIME	NA
BATTERY TYPE	NA
LED INDICATOR	NA
OPERATING TEMP.	-20/45°C
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

DESCRIPTION

- 3 inch Slim Down light 5CCT 5W 350LM

INSTALLATION

Compatible with 3 Inch Mounting Plate

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-5% dimming to choose the desired brightness.
Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

UL Listed. for Wet Location Energy Star. Title24.

