

DESCRIPTION

This 2-inch canless and trimless LED recessed light provides a clean, modern architectural look with a seamless ceiling finish. Designed for versatile residential and commercial applications, it is IC-rated for direct contact with insulation, ETL Listed, and suitable for wet locations. The fixture features 5 selectable CCT options for flexible color temperature selection and is JA8 compliant, meeting California's energy-efficiency requirements for high-quality LED lighting



BASED ON SAMPLE SETTING. ACTUAL LUMEN MAY VARY.

MODEL#	SIZE	WATTAGE	5CCT	LUMEN
RY-SQ-TRIMLESS-WH	2inch 15W		2700K	865lm
			3000K	935lm
			3500K	965lm
			4000K	985lm
			5000K	1000lm

TECHNICAL SPECIFICATION


WATTAGE	15W
VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	90
BEAM ANGLE	38°
MATERIAL	Metal + Composite
LIFESPAN	≥50,000hours
DIMMABLE	Triac Dimmable
Lumen per Watt	66.7 lm / w
BASE	LED Module
AIR TIGHT	YES
FINISH	Matte White
BATTERY TYPE	NA
TYPE	IC Rated
OPERATING TEMP	-4 ~104°F
RATING	ETL Wet Locations / JA8 CA Title24
WARRANTY	5 year limited

KEY FEATURES

- IC rated, Air-Tight for Wet Locations
- Fast Installation. No Junction Box Needed
- Dimmable
- Two spring clips are included for secure attachment to any ceiling material

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness. This fixture is compatible with industry standard forward phase/ reverse phase TRIAC/ ELV dimmers.



COMPATIBLE MOUNTING PLATE



RY-UNIVERSAL PLATE