RAYCOS LIGHTING

PROJECT NAME _____ DATE _____

NOTE _____

MWP EXTERIOR WALL-MOUNT SERIES

MINI WALL PACK WITH PHOTOCELL

WATTAGE + CCT SELECTABLE | PHOTOCELL PREINSTALLED



BLACK FINISH | IK08 LENS



POWER
15 / 20 / 25 W

OUTPUT
1,800 / 2,400 / 3,200 LM

COLOR
FIELD-SELECTABLE 3CCT

RATING
IP66 WET LOCATION

PERFORMANCE SPECIFICATIONS

SELECTABLE OUTPUT

Model	RY-HYA-MWP-962-3W3CCT
Power	15 / 20 / 25 W selectable
Lumen	1,800 / 2,400 / 3,200 lm selectable
CCT	3000 / 4000 / 5000 K or 3500 / 5000 / 6500 K
CRI	Ra > 90
Input	100-277 V AC, 50/60 Hz
Dimming	0-10 V
Operating temp	-4°F to +113°F (-20°C to +40°C)

DIMENSIONS

INCHES



CONSTRUCTION + PACKAGING

IP66 / IK08

Finish	Black
Lens	Frosted striped; IK08 vandal-resistant and UV-resistant
Location	Wet location rated (IP66)
Life	L70 at 50,000+ hours
Control	Photocell control preinstalled
DLC ID	DLC Premium (S-K4BGAD)
Pack qty.	10 fixtures per carton
Carton	15.35 x 13.18 x 9.65 in (390 x 335 x 245 mm)
Carton weight	15.65 lb (7.1 kg)

Intertek | DLC LISTED PREMIUM | IK08 RATED | Wet Location | Wattage Selectable | CCT Selectable | Dimmable | JA8 COMPLIANT

FIELD CONTROLS

POWER / PHOTOCELL / CCT

